

This Specification Data Sheet  
brought to you by:



15825 Trinity Blvd.

Fort Worth, Texas 76155

817/465-9494

[equipment@technicaldiagnostic.com](mailto:equipment@technicaldiagnostic.com)

[www.technicaldiagnostic.com](http://www.technicaldiagnostic.com)

[www.test-equipment-rental.com](http://www.test-equipment-rental.com)

<b>Model</b>	<b>230A</b>
<b>pH:</b>	
Range	-2.00 to 19.99
Resolution	0.01
Relative Accuracy	+/- 0.02
Slope	80 to 120%
Auto-Buffer-Recognition	4.01, 7.00, 10.01
<b>Temperature:</b>	
Range	-5.0 to 105.0 C
Resolution	0.1 C
Relative Accuracy	+/- 1.0 C
<b>Display:</b>	Custom LCD
<b>Inputs:</b>	One BNC, one pin tip, ATC, power
<b>Outputs:</b>	NA
<b>Power Requirements:</b>	One alkaline/lithium battery, or line adapter for 110 V, 220 V or 240 V
<b>Agency Approvals:</b>	CE, CSA, UL
<b>Environmental Requirements:</b>	5 to 45 C and 5 to 85% relative humidity, non-condensing
<b>Meter Dimensions:</b>	3.25 x 7.6 x 1.9 inches (w, l, d)
<b>Meter Case:</b>	Dust and splash resistant, chemical resistant